

FLAKE ICE MAKERS with sweet water or seawater Mod.series "S" evaporator without motocondensing unit

COMMERCIAL RANGE FROM 350 TO 4200 KG/24h

- Stainless steel base ASI 316
- Easy to installation and low operating costs
- Predisposed for connection to the motocondensing unit



MODEL	FT 350 S	FT 550 S	FT 800 S	FT 1200 S	FT 2000 S	FT 2800 S	FT 4000 S
Daily productivity (kg/24h)	320/380	450/580	720/870	1100/1300	1900/2150	2500/2900	3600/4200
Gear motor (watt)	90	90	110	110	110	110	120
Water consumption (lt/h)	15	24	36	54	89	120	175
Capacity KW (-30° / + 40°C)	1,7	2,9	4,5	7,4	11,9	16,5	19,5
Sizes (cm) width x depth x height	79x34x41	75x46x45	830x46x45	100x50x43	119x50x43	138x50x43	155x61x60
Weight (kg)	40	70	75	110	106	131	210

- FT 350 220/1/50 Hz - FT 550 S: Upon request 220/1/50 A. C.
- FT 350÷4000 S : Standard: 380/3/50 + N (Upon request: 24 Volt D. C.)
- Refrigerant: 448 A - 449 A
- Ice thickness: 2÷3mm
- Ice temperature: -14÷ -18

STANDARD EQUIPMENT

380/3/50 + -220/1/50 A. C.)= base in stainless steel - evaporator - gear reducer - automatic valve gas solenoid - thermostat - probes for water lack - electrical connection terminals

UPON REQUEST

Evaporator electrical resistance - ice conveyor - micro for super-full - stainless steel evaporator jacket saltwater dosing device - water level electroprobe

The 24-hour production index is based on a temperature of 24°C and supply water temperature of 18°C and may vary depending on installation conditions.